BATTERSEA LAMINATE FLOORING

Technical Data

XYLO flooring

Water Resistant Laminate Flooring

Description	Standard	Symbol	Requirements	Result
Wear resistance	EN 13329		AC3≥2000 revolutions; AC4≥4000 revolutions; AC5≥6000 revolutions	AC4
Thickness swelling	EN 13329		≤18%	9.1%
Dimensional variations after changes in relative humidity	EN 13329		≤0.9mm	δl≤0.38mm δw≤0.40mm
Impact resistance	EN 13329			Small ball:≥12N Large ball:≥750mm
Density	EN 323			940kg/m³
Resistance to staining	EN438			5 (groups 1+2) 4 (group 3)
Resistance to cigarette burns	EN438			4
Effect of a castor chair	EN425		25000 cycles, no damage	No change in appearance or damage
Effect of furniture leg	EN 424		No visible damage	No visible damage
Fire resistance	EN14041	Bs1-d0		Bfl-s1
Dynamic coefficient of friction	EN14041	DS	Dynamin coefficient of friction of ≥0.30 when tested and shalled be declared as technical calss DS	DS
CE certification	EN14041	CE	Refer to standard below	Pass
VOC	Floor Score	floor score		Pass

Dimensions 10 x196 x 1200mm
Packed 1.411m2
Installation See Box Inlay
Fitting 5G click
Bevel 4
Class 32

Warranty
Residential 25 years
Commercial 10 years

Underfloor Heating Systems
Suitable

QUALITY WARRANTY 10 years COMMERCIAL
QUALITY WARRANTY 25 years DOMESTIC
4 SIDES V-GROOVE
GEOTHERMAL
32
5G Licensed by Välinge
GREENGUARD GOLD
UFH UNDERFLOOR HEATING